

Speed, precision and ease of use.



Watch the video



P40 Bike

www.giuliano-automotive.com

NEW

**P40 BIKE**



1100 mm

510 mm

75 Kg

## DIGITAL ELECTRONIC WHEEL BALANCER WITH LED DISPLAY FOR MOTORCYCLE AND CAR WHEELS

- ✓ USB port for firmware updating via PC/notebook.



Advanced software for further upgrades\*



- ✓ Intuitive, Easy-to-use Control Panel.

- ✓ Complete with **HAWEKA** ProBike Eco Kit clamping adaptor for motorcycle wheels.


### FUNCTIONS

- Automatic static program selection (through motorcycle wheel automatic recognition).
- Static and dynamic balancing of car wheels and motorcycle wheels with single arm suspension.
- Self-diagnosis and self-calibration.
- OptiWeight (OW) system reduces the number of counterweights needed, by minimising static imbalance.



- ✓ Static balancing of motorcycle wheels with Probike Eco Kit.

### SPECIAL ALU PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.

- ✓ Pedal brake.

- ✓ Complete with cones and quick clamping ring nut for passengers car wheels.



Space-saving wheel guard (available as optional).

### HIDDEN WEIGHT



- Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

### OPPOSIT POSITION - OPPOSITE WEIGHT FUNCTION (OPF)



- Opposite Weight function (OPF), enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (at 6:00), easier to reach when you apply stick-on weight manually.

*\*The performance of the machine over time can improve, thanks to targeted updates.*

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

### OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter and much more

Find out more on our website !

### STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	110 Volt
Unbalance detection time	4,7 sec. (5 3/4"x14") 15 kg.
Balancing speed	< 150 rpm
Balancing precision	+ 1 g
Net weight	87 kg
Max. overall dimensions	1050x570x950 mm

### STANDARD ACCESSORIES

