

Integrated Sonar, Led light, Laser Line. BE FASTER and more productive!

NEW
P44



1100 mm 510 mm 75 Kg



COMING SOON



P44

www.giuliano-automotive.com



DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH LED DISPLAY, LASER LINE AND LED LIGHT

- Complete with wheel guard, cones and quick clamping ring nut.



Advanced software for further upgrades*.

- LED display built into the weight holder.

- Intuitive, Easy-to-use Control Panel.

- USB port for firmware updating via PC/notebook.

FUNCTIONS

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- Self-diagnosis and Self-calibration

LASER LINE

for exact positioning of adhesive weights.


LED LIGHT

to illuminate working area.



- Automatic measuring of wheel width by **SONAR (TW)**, standard.

SPECIAL ALU PROGRAM



Programs for selecting the best correction planes for any kind and shape of alloy rim.

SELF SELECTION MODE



Self-recognition of the Working program.



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

- Automatic electric brake.

HIDDEN WEIGHT



• Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE



• Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (6 o'clock), easier and more accessible, by a Laser line indicator.

*The performance of the machine over time can improve, thanks to targeted updates.

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website !

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	110Volt
Unbalance detection time	4,7 sec. (5 3/4"x14") 15 kg.
Balancing speed	< 150 rpm
Balancing precision	+ 1 g
Net weight with guard	97 kg
Max. overall dimensions	1350x1150x1280±1540 mm

STANDARD ACCESSORIES



- Wheel guard
- Set of 42-140 mm cones and quick clamping ring nut
- Manual gauge for measuring wheel rim width
- Counterweight pliers
- SONAR TW**