


Pneumatic clamping, Integrated Sonar, Led light, Laser Line.

NEW
P45 Plus



P45 Plus

www.giuliano-automotive.com

DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH LED DISPLAY, PNEUMATIC CLAMPING, LASER LINE AND LED LIGHT



Advanced software for further upgrades.

Complete with wheel guard, standard.

FUNCTIONS

- Automatic measuring of wheel diameter and distance.
- Automatic START and STOP.
- Pneumatic wheel clamping.
- Static and dynamic balancing.
- OPTIMATCH function.
- Self-diagnosis and self-calibration.
- USB port for firmware updating via PC/notebook.

Available with **automatic** weight placement position **search function** (ref. P46 Plus).

Tools Storage Box (standard).

LASER LINE

for exact positioning of adhesive weights, standard.

LED LIGHT

on working area, standard.

HIDDEN WEIGHT



• Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE



• Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (6 o'clock), easier and more accessible, by a Laser line indicator.

The performance of the machine over time can improve, thanks to targeted updates.

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

[Find out more on our website !](#)

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	110Volt
Unbalance detection time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	+ 1 g
Operating pressure	8 -10 bar (115-145 PSI)
Net weight with guard	102 Kg
Max. overall dimensions	1450x1150x1280±1540 mm

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

STANDARD ACCESSORIES



- Wheel guard
- Set of 42-140 mm cones and pneumatic clamping system
- Manual gauge for measuring wheel rim width
- Counterweight pliers
- SONAR TW




PNEUMATIC WHEEL CLAMPING



Complete with cones and pneumatic clamping system.

Automatic wheel width measurement via **SONAR (TW)**, standard.

SPECIAL ALU-S PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.

SELF SELECTION MODE



Self-recognition of the Working program.

Two-position pedal.

Pneumatic wheel lock through pedal control.

Automatic electric brake in weight placement position.

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).