


Pneumatic clamping, Integrated Sonar, Led light, Laser Line.

NEW
P45



COMING SOON



P45 Plus

www.giuliano-automotive.com

DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH LED DISPLAY, LASER LINE AND LED LIGHT



Advanced software for further upgrades.

Complete with wheel guard, standard.

Automatic wheel width measurement via **SONAR (TW)**, standard.

FUNCTIONS

- Automatic measuring of wheel diameter and distance.
- Automatic START and STOP.
- Static and dynamic balancing. OPTIMATCH function.
- Self-diagnosis and self calibration.
- USB port for firmware updating via PC/notebook.

Available with **automatic** weight placement position **search function** (ref. **P46 Plus**).

Tools Storage Box (standard).

LASER LINE

for exact positioning of adhesive weights, standard.

LED LIGHT

on working area, standard.

HIDDEN WEIGHT



Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE



Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (6 o'clock), easier and more accessible, by a Laser line indicator.

The performance of the machine over time can improve, thanks to targeted updates.

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

[Find out more on our website !](#)

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	110Volt
Unbalance detection time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	+ 1 g
Operating pressure	8 - 10 bar (115-145 PSI)
Net weight with guard	102 Kg
Max. overall dimensions	1450x1150x1280±1540 mm

EXTENSIVE SELECTION OF STANDARD ACCESSORIES


STANDARD ACCESSORIES



- Wheel guard
- Set of 42-140 mm cones
- Manual gauge for measuring wheel rim width
- Counterweight pliers
- **SONAR TW**



SPECIAL ALU-S PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.

SELF SELECTION MODE



Self-recognition of the Working program.

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

Two-position pedal.

Pneumatic wheel lock through pedal control.

Automatic electric brake in weight placement position.